



CONNECT
Posi-Shell® Technology

The most economic solution for moderate erosion control and hydroseeding needs.

Game changing ease of mixing, application and performance.

The natural mineral-based science in Connect provides a user-friendly product that is unmatched in the marketplace. It has superior bonding strength, both seed and soil, compared to other products within this performance category.

Connect is simple to pour, requires no manual or mechanical shredding and it will not clump. Connect, instantaneously consumes water which allows for its immediate wet-out and creation of a uniform slurry with minimal water and mixing time.

Our one-of-a-kind performance characteristics include the highest loading rates, no slurry separation (even overnight) and increased speed of application to go along with superb ground coverage. It's truly a game changer!



Incredible savings... for increased bottom line!

Only 85 gallons of water per 50 lb. of Connect!

Increased speed of application and superb ground coverage!



CONNECT

Posi-Shell® Technology

- Prevents Erosion
- Increases Moisture Retention
- Accelerates Germination



- Easy Handling
- Quick Loading
- Fast Mixing
- No Separation
- Better Coverage

Contact us today for more information.



Reduce your water requirements, lower your labor costs, boost your results and increase your return on investment.

Connect is simple to pour, requires no shredding, and will not clump. It consumes water instantaneously, allowing for immediate wet-out and creation of a uniform slurry with minimal water and mixing time.

Connect's best in class performance characteristics include the highest loading rates, no slurry separation (even overnight), increased application speed and superb ground coverage. It's truly a game changer!

Connect Application Rates				
Slope	≤ 5:1	4:1	3:1	≤ 2.5:1
Lbs. Per Acre	2,000	2,500	3,000	3,500
Kg. Per Hectare	2,242	2,803	3,363	3,924

Connect Loading Chart					
		Loads Per Acre – Based On Slope			
Machine Size (Gallons)	Bags Per Load	≤ 5:1	4:1	3:1	≤ 2.5:1
500	6	6.7	8.3	10	11.7
1,000	12	3.3	4.2	5	5.8
1,500	18	2.2	2.8	3.3	3.9
3,000	37	1.1	1.4	1.6	1.9
4,000	49	0.8	1.0	1.2	1.4

For technical services or to locate your nearest Connect dealer:



Call: **1-800-800-7671** • Email: **Sales@LSCenv.com**
 Visit LSC online at: **www.LSCenv.com**
LSC Environmental Products, LLC
 2183 Pennsylvania Ave., Apalachin, NY 13732

Information and statements herein are believed to be reliable but are not to be constructed as a warranty or guarantee. Some extreme situations may require higher application rates. LSC Environmental Products, LLC offers no warranties, express or implied. Nothing herein is to be taken as permission to practice any patented invention without a license. Connect is a registered trademark of LSC Environmental Products, LLC. All rights reserved. © 2016 LSC Environmental Products, LLC